

Internet Engineering Task Force (IETF)  
Request for Comments: 6485  
Category: Standards Track  
ISSN: 2070-1721

G. Huston  
APNIC  
February 2012

The Profile for Algorithms and Key Sizes for  
Use in the Resource Public Key Infrastructure (RPKI)

Abstract

This document specifies the algorithms, algorithms' parameters, asymmetric key formats, asymmetric key size, and signature format for the Resource Public Key Infrastructure (RPKI) subscribers that generate digital signatures on certificates, Certificate Revocation Lists, and signed objects as well as for the relying parties (RPs) that verify these digital signatures.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6485>.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## 1. Introduction

This document specifies:

- \* the digital signature algorithm and parameters;
- \* the hash algorithm and parameters;
- \* the public and private key formats; and,
- \* the signature format

used by Resource Public Key Infrastructure (RPKI) subscribers when they apply digital signatures to certificates, Certificate Revocation Lists (CRLs), and signed objects (e.g., Route Origin Authorizations (ROAs) and manifests). Relying parties (RPs) also use the algorithms defined in this document to verify RPKI subscribers' digital signatures [RFC6480].

This document is referenced by other RPKI profiles and specifications, including the RPKI Certificate Policy (CP) [RFC6484], the RPKI Certificate Profile [RFC6487], the SIDR Architecture [RFC6480], and the Signed Object Template for the RPKI [RFC6488]. Familiarity with these documents is assumed.

### 1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

## 2. Algorithms

Two cryptographic algorithms are used in the RPKI:

- \* The signature algorithm used in certificates, CRLs, and signed objects is RSA Public-Key Cryptography Standards (PKCS) #1 Version 1.5 (sometimes referred to as "RSASSA-PKCS1-v1\_5") from Section 5 of [RFC4055].
- \* The hashing algorithm used in certificates, CRLs, and signed objects is SHA-256 [SHS]. The hashing algorithm is not identified by itself when used in certificates and CRLs, as they are combined with the digital signature algorithm (see below).

When used in the Cryptographic Message Syntax (CMS) SignedData, the hash algorithm (in this case, the hash algorithm is sometimes called a message digest algorithm) is identified by itself. For CMS SignedData, the object identifier and parameters for SHA-256 (as defined in [RFC5754]) MUST be used

when populating the `digestAlgorithms` and `digestAlgorithm` fields.

NOTE: The exception to the above hashing algorithm is the use of SHA-1 [SHS] when Certification Authorities (CAs) generate authority and subject key identifiers [RFC6487].

When used to generate and verify digital signatures the hash and digital signature algorithms are referred together, i.e., "RSA PKCS#1 v1.5 with SHA-256" or more simply "RSA with SHA-256". The Object Identifier (OID) `sha256withRSAEncryption` from [RFC4055] MUST be used.

Locations for this OID are as follows:

In the certificate, the OID appears in the signature and `signatureAlgorithm` fields [RFC4055];

In the CRL, the OID appears in the `signatureAlgorithm` field [RFC4055];

In CMS SignedData, the OID appears in each `SignerInfo` `signatureAlgorithm` field [RFC3370] using the OID from above; and,

In a certification request, the OID appears in the PKCS #10 `signatureAlgorithm` field [RFC2986] or in the Certificate Request Message Format (CRMF) `POPOSigningKey` signature field [RFC4211].

### 3. Asymmetric Key Pair Formats

The RSA key pairs used to compute the signatures MUST have a 2048-bit modulus and a public exponent (*e*) of 65,537.

#### 3.1. Public Key Format

The subject's public key is included in `subjectPublicKeyInfo` [RFC5280]. It has two sub-fields: `algorithm` and `subjectPublicKey`. The values for the structures and their sub-structures follow:

`algorithm` (which is an `AlgorithmIdentifier` type):

The object identifier for RSA PKCS#1 v1.5 with SHA-256 MUST be used in the `algorithm` field, as specified in Section 5 of [RFC4055]. The value for the associated parameters from that clause MUST also be used for the `parameters` field.

`subjectPublicKey`:

`RSAPublicKey` MUST be used to encode the certificate's `subjectPublicKey` field, as specified in [RFC4055].

### 3.2. Private Key Format

Local policy determines the private key format.

### 4. Signature Format

The structure for the certificate's signature field is as specified in Section 1.2 of [RFC4055]. The structure for the CMS SignedData's signature field is as specified in [RFC3370].

### 5. Additional Requirements

It is anticipated that the RPKI will require the adoption of updated key sizes and a different set of signature and hash algorithms over time, in order to maintain an acceptable level of cryptographic security to protect the integrity of signed products in the RPKI. This profile should be replaced to specify such future requirements, as and when appropriate.

CAs and RPs SHOULD be capable of supporting a transition to allow for the phased introduction of additional encryption algorithms and key specifications, and also accommodate the orderly deprecation of previously specified algorithms and keys. Accordingly, CAs and RPs SHOULD be capable of supporting multiple RPKI algorithm and key profiles simultaneously within the scope of such anticipated transitions. The recommended procedures to implement such a transition of key sizes and algorithms is not specified in this document.

### 6. Security Considerations

The Security Considerations of [RFC4055], [RFC5280], and [RFC6487] apply to certificates and CRLs. The Security Considerations of [RFC5754] apply to signed objects. No new security threats are introduced as a result of this specification.

### 7. Acknowledgments

The author acknowledges the reuse in this document of material originally contained in working drafts of the RPKI Certificate Policy [RFC6484] and the resource certificate profile [RFC6487] documents. The co-authors of these two documents, namely Stephen Kent, Derrick Kong, Karen Seo, Ronald Watro, George Michaelson, and Robert Loomans, are acknowledged, with thanks. The constraint on key size noted in this profile is the outcome of comments from Stephen Kent and review comments from David Cooper. Sean Turner has provided additional review input to this document.

## 9. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2986] Nystrom, M. and B. Kaliski, "PKCS #10: Certification Request Syntax Specification Version 1.7", RFC 2986, November 2000.
- [RFC3370] Housley, R., "Cryptographic Message Syntax (CMS) Algorithms", RFC 3370, August 2002.
- [RFC4055] Schaad, J., Kaliski, B., and R. Housley, "Additional Algorithms and Identifiers for RSA Cryptography for use in the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 4055, June 2005.
- [RFC4211] Schaad, J., "Internet X.509 Public Key Infrastructure Certificate Request Message Format (CRMF)", RFC 4211, September 2005.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, May 2008.
- [RFC5754] Turner, S., "Using SHA2 Algorithms with Cryptographic Message Syntax", RFC 5754, January 2010.
- [RFC6480] Lepinski, M. and S. Kent, "An Infrastructure to Support Secure Internet Routing", RFC 6480, February 2012.
- [RFC6484] Kent, S., Kong, D., Seo, K., and R. Watro, "Certificate Policy (CP) for the Resource Public Key Infrastructure (RPKI)", BCP 173, RFC 6484, February 2012.
- [RFC6487] Husotn, G., Michaelson, G., and R. Loomans, "A Profile for X.509 PKIX Resource Certificates", RFC 6487, February 2012.
- [RFC6488] Lepinski, M., Chi, A., and S. Kent, "Signed Object Template for the Resource Public Key Infrastructure (RPKI)", RFC 6488, February 2012.
- [SHS] National Institute of Standards and Technology (NIST), "FIPS Publication 180-3: Secure Hash Standard (SHS)", FIPS Publication 180-3, October 2008.

Author's Address

Geoff Huston  
APNIC

EMail: [gih@apnic.net](mailto:gih@apnic.net)